

CONSTRUCTION PRODUCTS REGULATION DECLARATION of PERFORMANCE

Product Identification:	Multipanel® 11mm Laminate faced wall panel Collections
Type:	All standard grades
Intended use:	Wood-based panels for use in construction – Characteristics, evaluation of conformity and marking
Company:	Grant Westfield Westfield Avenue Edinburgh United Kingdom EH11 2QH
System of Assessment and Verification of Constancy of Performance (AVCP):	System 4
Provisions:	EN 13986:2004 Wood-based panels for use in construction – Characteristics, evaluation of conformity and marking
	EN 622-5:2009 Meditate exterior grade MDF for use in humid conditions
	EN 438-3:2005 High-pressure decorative laminates (HPL). Sheets based on thermosetting resins (usually called laminates). Classification and specifications for laminates less than 2mm thick intended for bonding to supporting substrates


Essential Characteristics:	Test Method	Standard	Measure
Bonding Strength	EN 319	EN 622 part 5	1.2 N/mm ²
Modulus of Rupture	EN 310	EN 622 part 5	40 N/mm ²
Modulus of Elasticity	EN 310	EN 622 part 5	4000 N/mm ²
Durability	BS 4965	Class D4	-
Thickness tolerance	EN 324-1	EN 622 part 5	+/-0.15 mm
Reaction to fire	EN 13501-1	EN 438:2005	D-s2, d0
Water Vapour Permeability	EN 12572:2001	-	70 wet / 200 dry
Formaldehyde Emission	EN 120	CARB Phase 2	< 1mg per 100g

The performance of the product identified for the type specified is in conformity with the declared performance in the essential characteristics above.

The declaration of performance is issued under the sole responsibility of Norcross Group (Holdings) Ltd T/A Grant Westfield.

Signed for and on behalf of Norcross Group (Holdings) Ltd T/A Grant Westfield by: **John Mortimer**, Managing Director

SIGNATURE:



DATE AND PLACE OF ISSUE:

Edinburgh on 15 November