

The UK's leading bathroom wall panels

CONSTRUCTION PRODUCTS REGULATION DECLARATION of PERFORMANCE

Product Identification:		Multipanel® 11mm Laminate faced wall panel Collections			
Type:		All standard grades			
Intended use:		Wood-based panels for use in construction – Characteristics,			
		evaluation of conformity and marking			
Company: System of Assessment and Verification of		Grant Westfield			
		Westfield Avenue Edinburgh			
				United Kingdom EH11 2QH	
		System 4			
		Constancy of Performance		oyoto	
Provisions:		EN 13986:2004			
		Wood-based panels for use in construction – Characteristics,			
		evaluation of conformity and marking			
		EN 622-5:2009			
		Medite exterior grade MDF for use in humid conditions			
		EN 438-3:2005 High-pressure decorative laminates (HPL). Sheets based on thermosetting resins (usually called laminates). Classification and			
				specifications for laminates less than 2mm thick intended for bonding to supporting substrates	
		Essential Characteristics:	Test Method	Standard	Measure
Bonding Strength	EN 319	EN 622 part 5	1.2 N/mm2		
Modulus of Rupture	EN 310	EN 622 part 5	40 N/mm2		
Modulus of Elasticity	EN 310	EN 622 part 5	4000 N/mm2		
Durability	BS 4965	Class D4	-		
Thickness tolerance	EN 324-1	EN 622 part 5	+/-0.15 mm		
Reaction to fire	EN 13501-1	EN 438:2005	D-s2, d0		
Water Vapour Permeability	EN 12572:2001	-	70 wet / 200 dry		

The performance of the product identified for the type specified is in conformity with the declared performance in the essential characteristics above.

CARB Phase 2

Issued: 15/09/2025

The declaration of performance is issued under the sole responsibility of Norcros Group (Holdings) Ltd T/A Grant Westfield.

Signed for and on behalf of Norcros Group (Holdings) Ltd T/A Grant Westfield by: John Mortimer, Managing Director

SIGNATURE:

Formaldehyde Emission

DATE AND PLACE OF ISSUE: