



MULTIPANEL®

Don't tile it. Multipanel it.

Construction products regulation Declaration of performance

Product Identification:	Multipanel® Walls Tile Range
Type:	Standard Grade HPL Composite Panels
Intended use:	Internal wall panelling
Company:	Grant Westfield Ltd Westfield Avenue Edinburgh United Kingdom EH11 2QH
System of assessment and verification of constancy of performance (AVCP):	System 4
Provisions:	EN 438-7 High-pressure decorative laminates (<i>HPL</i>) – Sheets based on thermosetting resins (<i>Usually called Laminates</i>) – Part 7: Compact laminate and HPL composite panels for internal and external wall and ceiling finishes.

Essential characteristics	Performance
Reaction to Fire	D-s2,d0
Fire resistance	NPD
Water vapour permeability	110 wet / 250 dry
Resistance to fixings	>250N
Direct airborne sound insulation	NPD
Bonding strength	NPD
Flexural tensile strength	>90MPa
Flexural modulus	>9MPa
Thermal conductivity	0.25 W/m.°K
Content of pentachlorophenol	N/A
Release of Formaldehyde	Class E1
Sound absorption	NPD
Durability - Resistance to wet conditions - Density	<6% >1350kg/m ³

The performance of the product identified for the type specified is in conformity with the declared performance in the essential characteristics above.

The declaration of performance is issued under the sole responsibility of Grant Westfield Ltd.

Signed for and on behalf of Grant Westfield Ltd by:

Sarah McLean, Managing Director

SIGNATURE:

DATE AND PLACE OF ISSUE
Edinburgh on 08 March 2018

Multipanel® is part of the Grant Westfield Group