

## CONSTRUCTION PRODUCTS REGULATION DECLARATION of PERFORMANCE

<b>Product Identification:</b>	<b>Multipanel® Walls Tile Range</b>
<b>Type:</b>	Standard Grade HPL Composite Panels
<b>Intended use:</b>	Internal wall panelling
<b>Company:</b>	Grant Westfield Ltd Westfield Avenue Edinburgh United Kingdom EH11 2QH
<b>System of assessment and verification of constancy of performance (AVCP):</b>	<b>System 4</b>
<b>Provisions:</b>	<b>EN 438-7</b> High-pressure decorative laminates (HPL) – Sheets based on thermosetting resins (Usually called Laminates) – Part 7: Compact laminate and HPL composite panels for internal and external wall and ceiling finishes.

Essential characteristics	Performance
Reaction to Fire	D-s2,d0
Fire resistance	NPD
Water vapour permeability	110 wet / 250 dry
Resistance to fixings	>250N
Direct airborne sound insulation	NPD
Bonding strength	NPD
Flexural tensile strength	>90MPa
Flexural modulus	>9MPa
Thermal conductivity	0.25 W/m.°K
Content of pentachlorophenol	N/A
Release of Formaldehyde	Class E1
Sound absorption	NPD
Durability	<6%
- Resistance to wet conditions	>1350kg/m3
- Density	

The performance of the product identified for the type specified is in conformity with the declared performance in the essential characteristics above.

The declaration of performance is issued under the sole responsibility of Grant Westfield Ltd.

Signed for and on behalf of Grant Westfield Ltd by: **Sarah Law**, Managing Director

SIGNATURE: 

DATE AND PLACE OF ISSUE  
Edinburgh on 4 January 2022

Multipanel® is a registered trademark of Grant Westfield Limited